

# DeFelsko®

## Wet Film Thickness Gage Series

Notched Wet Film Thickness Gages measure the thickness of paint, enamels, and other wet films quickly and accurately

Select from 3 styles

### Certified Stainless 8-Sided WFT Gage

Rotating dual-head design measures up to 1,500 µm of coating on one side and 60 mils of coating on the reverse.

- Durable stainless steel construction
- Includes Certificate of Accuracy
- 40 notches for superior resolution — 5 notches per side
- Two-sided—microns and mils
  - 1–1,500 microns / 1–60 mils
- Includes compact hard-shell storage case and pictorial instruction card



### Stainless 6-Sided WFT Gages

24- or 36-notch wet film gages for measuring up to 3,000 µm or 120 mils of coating

- Durable stainless steel construction
- Select from 6 measurement ranges
- Imperial versions include features for confirming 1/16" & 1/8" edge radius and edge chamfers (NACE SP0178, PA Guide 11)
- Metric versions include a notch for confirming 2 mm edge radius (ISO 8501-3)
- Includes compact hard-shell storage case and pictorial instruction card



### Aluminum 4-Sided WFT Gages

30-notch wet film gages for measuring up to 2,000 µm or 80 mils

- Economical aluminum construction
- Convenient 5.7 x 8.25 cm (2.25" x 3.25") card format
- Can be discarded, kept as a record of film thickness, or cleaned and reused
- Sold in packs of 10
- Select from microns or mils
  - 25–2,000 microns (WFG2000AL10PK)
  - 1–80 mils (WFG80AL10PK)



Stainless 6-Sided Wet Film Thickness Gage

#### Ordering Guide

| Certified Stainless 8-Sided Wet Film Thickness Gage |               |
|---|---------------|
| Wet Film Gage, 60 mils / 1,500 µm                   | WFG60/1500SSC |
| Stainless 6-Sided Wet Film Thickness Gages          |               |
| 20–370 µm   | WFG370SS      |
| 25–2,000 µm   | WFG2000SS     |
| 25–3,000 µm   | WFG3000SS     |
| 0.5–15 mils   | WFG15SS       |
| 1–80 mils   | WFG80SS       |
| 1–120 mils  | WFG120SS      |
| Aluminum 4-Sided Wet Film Thickness Gages           |               |
| 25–2,000 µm (10 pack)                               | WFG2000AL10PK |
| 1–80 mils (10 pack)                                 | WFG80AL10PK   |

Conforms to ISO 2808, ASTM D4414, AS/NZS 1580.107.3, JIS K 5600-1-7, NF T30-125, US NAVY PPI 63101-000, US NAVY NSI 009-32 and others.

**DeFelsko®**  
Inspection Instruments

**DeFelsko Corporation** • 800 Proctor Ave., Ogdensburg, New York 13669-2205 USA  
Toll Free **1-800-448-3835** • Tel: +1-315-393-4450  
techsale@defelsko.com • www.defelsko.com

© DeFelsko Corporation USA 2024. All Rights Reserved. Technical Data subject to change without notice. Printed in USA. PGV.LW/W2402

Distributed by:



AB: (587) 758-8367 • ON: (905) 688-5800 • info@stone-tucker.com • www.stone-tucker.com