
# INKER & MASOR MODEL APS



Holiday Detector 800v to 35,000v

SAFETY SHUT OFF, INTEGRATED VOLTMETER, LED HOLIDAY INDICATOR, ERGONOMIC DESIGN, VOLUME CONTROL AND A <u>NEW, LIGHTWEIGHT,</u> LONG LIFE BATTERY

**DESIGNED WITH SAFETY IN MIND!** 



Distributed by



Instrument will work only when safety handle is depressed.



Integrated voltmeter povides measured output voltage. No need for additional, separate voltmeter for verification

www.detectron.com

www.teststations.com

Info@tinker-rasor.com

www.tinker-rasor.com

Tinker & Rasor quality is found in our products, our people and our customer service.







### INKER & RASOR

#### CORROSION MITIGATION INSTRUMENTATION

## PRODUCT DATA SHEET MODEL APS HOLIDAY DETECTOR

#### Features:

- SAFETY SWITCH INSTANT SHUT OFF
- Updated Battery light weight, longer life
- 800v 35000v in one instrument
- Integrated Voltmeter
- Volume adjustment for use in loud environments
- Super Bright visual holiday indicator
- Ergonomic handle and grip
- Low battery voltage indicator
- Regulated voltage
- Push button operation

#### **Construction:**

- Rugged design for long life
- Water & Dust Resistant Carrying Case
- Weather sealed
- · Solid state electronics

#### **Applications:**

- Pipelines and other coated structures
- · Wide variety of coatings materials
- Thin to thick coatings
- Conforms to NACE International SP0188, SP0274, Sp0490 Also to many ASTM, SSPC, ISO, etc

#### **Specifications:**

- Pulse DC output voltage
- Low: 800v to 8,000v
- High: 3,500v to 35,000v
- 100v Resolution (Voltmeter)
- +/- 5% Accuracy
- Battery operated (6v)
- 110/220v AC Charger

#### **Dimensions:**

- 2.5" x 21.5" x 2.75" Instrument only
- 5" x 2.5" x 5.5" Battery box

#### **Carrying Case:**

40.5" x 17" x 7" (1028.7 x 431.8 x 177.8 mm) 40 lbs. (18.14kg) Shipping Weight\* \*Weight will vary based upon electrode choices

DELIVERY: Immediately from STOCK

ExWorks San Bernardino, CA USA

SERVICE: **24-hour Turn-Around** 

TERMS: Net30 Days, on approval of credit

WARRANTY: 3 Years, parts and labor



Kit Includes:
Instrument
(2) Batteries, w/ Cover
Ground Cable
Wand Handle
Inspection Paddle
Carrying Case
Instruction Manual
Letter of Calibration

Electrode (Choose One):

Full Circle Spring Electrode for any one pipe diameter between 2" and 36"

Half Circle Spring Electrode for any one pipe, 0.75" and 8"

Silicone-Rubber Brush Electrode with any one width between 2" and 8"

#### MODEL APS HOLIDAY DETECTOR

AVAILABLE FROM STOCK